

| Model | S _{50%} (KVA) | U ₂₀ (V) | U _{1n} (V) | I _{2p} (KA) | I _{1p} (A) | Dimension | Weight (kg) | Cooling Flow Rate (Lit/Min) | Insulation Class | Frequency (HZ) | Application |
|----------|------------------------|---------------------|---------------------|----------------------|---------------------|-------------|-------------|-----------------------------|------------------|----------------|--|
| TPS015/0 | 15 | 3.8 | 380 | 2.8 | 28 | 128*96*313 | 15 | 4 | F | 50 | For welding Gun according to ISO5826 Standard & Geometric according to NovinSazan Standard |
| TPS020/0 | 20 | 4.5 | 380 | 3.2 | 38 | 128*96*343 | 19 | | | | |
| TP11 | 25 | 4.5 | 380 | 3.9 | 46 | 160*120*267 | 22 | | | | |
| TP12 | 30 | 5.6 | 380 | 3.9 | 58 | 160*120*282 | 24 | | | | |
| TP13 | 42 | 7 | 380 | 4.2 | 78 | 160*120*327 | 29 | | | | |
| TP15 | 50 | 8.4 | 380 | 4.2 | 93 | 160*120*372 | 34 | | | | |
| TPB050/0 | 50 | 8.4 | 380 | 4.2 | 93 | 174*145*380 | 44 | | | | |
| TP16 | 70 | 10.5 | 380 | 4.7 | 130 | 174*145*370 | 43 | | | | |
| TPJ036/0 | 36 | 6.3 | 400 | 4 | 62.5 | 160*125*231 | 21 | 4 | F | 50 | For welding Gun according to ISO5826 Standard & Geometric according to ISO10656 Standard |
| TPJ045/0 | 45 | 8 | 400 | 4 | 80 | 160*125*261 | 25 | | | | |
| TPJ054/0 | 51 | 7.1 | 400 | 5.1 | 91 | 160*125*279 | 28 | | | | |
| TPJ076/0 | 72 | 10 | 400 | 5.1 | 127.5 | 160*125*345 | 37 | | | | |
| TPJ103/0 | 97 | 13.5 | 400 | 5.1 | 170 | 160*125*411 | 47 | | | | |
| TSM135/0 | 135 | 9.5 | 400 | 10 | 238 | 250*209*487 | 120 | 8 | F | 50 | For Stationary Machine according to ISO5826 Standard |
| TSM135/1 | 108,80 | 4.75,6.35 | 400 | 12 | 142,190 | 250*209*487 | 120 | | | | |
| TSB155/0 | 155 | 24 | 400 | 4.55 | 273 | 250*209*712 | 125 | 8 | F | 50 | Suspended Transformers according to ISO5826 Standard |
| TSB190/0 | 190 | 33.3 | 400 | 4 | 333 | 250*209*837 | 175 | | | | |